

Schottky Diode

V_{RRM} = 80 V
 I_{FAV} = 2x 35 A
 V_F = 0,64 V


High Performance Schottky Diode

Low Loss and Soft Recovery


Common Cathode

Part number

DSSK70-008A



Backside: cathode



Features / Advantages:

- Very low V_F
- Extremely low switching losses
- Low I_{rm} values
- Improved thermal behaviour
- High reliability circuit operation
- Low voltage peaks for reduced protection circuits
- Low noise switching

Applications:

- Rectifiers in switch mode power supplies (SMPS)
- Free wheeling diode in low voltage converters

Package: TO-247

- Industry standard outline
- RoHS compliant
- Epoxy meets UL 94V-0

Disclaimer Notice


Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at www.littelfuse.com/disclaimer-electronics.

Schottky

Symbol	Definition	Conditions	Ratings			
			min.	typ.	max.	
V_{RSM}	max. non-repetitive reverse blocking voltage	$T_{VJ} = 25^\circ C$			80	V
V_{RRM}	max. repetitive reverse blocking voltage	$T_{VJ} = 25^\circ C$			80	V
I_R	reverse current, drain current	$V_R = 80 V$ $V_R = 80 V$	$T_{VJ} = 25^\circ C$ $T_{VJ} = 125^\circ C$		2 10	mA
V_F	forward voltage drop	$I_F = 35 A$ $I_F = 70 A$ $I_F = 35 A$ $I_F = 70 A$	$T_{VJ} = 25^\circ C$ $T_{VJ} = 125^\circ C$		0,76 0,90 0,64 0,80	V
I_{FAV}	average forward current	$T_C = 140^\circ C$ rectangular $d = 0.5$	$T_{VJ} = 175^\circ C$		35	A
V_{F0} r_F	threshold voltage slope resistance } for power loss calculation only		$T_{VJ} = 175^\circ C$		0,43 4,3	V mΩ
R_{thJC}	thermal resistance junction to case				0,5	K/W
R_{thCH}	thermal resistance case to heatsink			0,25		K/W
P_{tot}	total power dissipation		$T_C = 25^\circ C$		300	W
I_{FSM}	max. forward surge current	$t = 10 \text{ ms}; (50 \text{ Hz}), \text{sine}; V_R = 0 V$	$T_{VJ} = 45^\circ C$		700	A
C_J	junction capacitance	$V_R = 12V$ f = 1 MHz	$T_{VJ} = 25^\circ C$		1,05	nF


Package TO-247

Symbol	Definition	Conditions	Ratings		
			min.	typ.	max.
I_{RMS}	RMS current	per terminal ¹⁾			70 A
T_{VJ}	virtual junction temperature		-55		175 °C
T_{op}	operation temperature		-55		150 °C
T_{stg}	storage temperature		-55		150 °C
Weight				6	g
M_d	mounting torque		0,8		1,2 Nm
F_c	mounting force with clip		20		120 N


Product Marking


Ordering	Ordering Number	Marking on Product	Delivery Mode	Quantity	Code No.
Standard	DSSK70-008A	DSSK70-008A	Tube	30	478776


Similar Part	Package	Voltage class
DSSK70-008AR	ISOPLUS247 (3)	80

Equivalent Circuits for Simulation
^{* on die level}
 $T_{VJ} = 175^\circ\text{C}$

Schottky

$V_{0\ max}$	threshold voltage	0,43	V
$R_{0\ max}$	slope resistance *	1,7	

Outlines TO-247


Sym.	Inches min. max.	Millimeter min. max.
A	0.185 0.209	4.70 5.30
A1	0.087 0.102	2.21 2.59
A2	0.059 0.098	1.50 2.49
D	0.819 0.845	20.79 21.45
E	0.610 0.640	15.48 16.24
E2	0.170 0.216	4.31 5.48
e	0.215 BSC	5.46 BSC
L	0.780 0.800	19.80 20.30
L1	- 0.177	- 4.49
Ø P	0.140 0.144	3.55 3.65
Q	0.212 0.244	5.38 6.19
S	0.242 BSC	6.14 BSC
b	0.039 0.055	0.99 1.40
b2	0.065 0.094	1.65 2.39
b4	0.102 0.135	2.59 3.43
c	0.015 0.035	0.38 0.89
D1	0.515 -	13.07 -
D2	0.020 0.053	0.51 1.35
E1	0.530 -	13.45 -
Ø P1	- 0.29	- 7.39




Schottky


Fig. 1 Max. forward voltage drop characteristics




Fig. 2 Typ. reverse current I_R vs. reverse voltage V_R




Fig. 3 Typ. junction capacitance C_T vs. reverse voltage V_R




Fig. 4 Average forward current $I_{F(AV)}$ vs. case temp. T_C





Fig. 5 Forward power loss characteristics



Note: All curves are per diode

Fig. 6 Transient thermal impedance junction to case at various duty cycles